- \$1

D. No.

# INDIAN INSTITUTE OF TECHNOLOGY(ISM) D H A N B A D - 826 004

### **CAMPUS MAINTENANCE UNIT**

No.: Maint/958039/18-19

Date : 11.05.2018

Name of work - A/R & Maintenance work (Inside) at Topaz Hostel.			
Issued to I	o M/s	of	
	on deposit of	cost of ₹500/- vide	
C.R. No	dated		
	The tender documents carrying follow	ng papers :-	
(1)	Notice Inviting Tenders		
(2)	Item Rate Tender for works		
(3)	Schedule of Materials/Qtty.	- 10 m2	
(4)	Terms & Conditions of Contractor		

Campus Engineer

The

# INDIAN INSTITUTE OF TECHNOLOGY (ISM) DHANBAD-826004 (CAMPUS MAINTENANCE UNIT)

#### NOTICE INVITING TENDER

### No. Maint/958039/18-19

1. Tenders in the prescribed form are hereby invited from the Registered contractors of Indian Institute of Technology (ISM) for "A/R & Maintenance work (Inside) at Topaz Hostel.".

Date: 11.05.2018

### Estimated cost ₹4,98,007.00

- 2. The form of tenders consisting of the details plans, complete specifications, the schedule of quantity of the various works to be done and the set of "conditions of contract" to be complied with by the person whose tenders may be accepted, which will also be found in the form of tenders, can be obtained at the office of CMU between 10 am to 4 pm every day except on Holidays and can be download from IIT(ISM) website <a href="www.iitism.ac.in">www.iitism.ac.in</a> on payment of ₹ 500.00 in cash counter of IIT (ISM).Demand Draft to a Nationalised Bank in favour of "Registrar, IIT (ISM) Dhanbad".
- 3. The site of the work is available/or the site of the work will be made available in parts as specified below.
- 4. Tender which should always be placed in sealed cover with the name of the work written on the envelopes will be received by Campus Engineer and opened in his office as per details given below.

Last date of receipt/submission of Tender 23.05.2018 up to 3.00 P.M.

Date and time of opening of Tender 23.05.2018 at 4.00 P.M.

- 5. The time allowed for the work will be **45 (Forty five) DAYS** from the 10th day after the date of written order to commence the work.
- 6. CPWD specification will be followed strictly during execution.
- 7. The contractors should quote in figures as well as in words the rate and amount tendered by them. The amount for each item should be worked out and requisite total given.
- 8. The last date for issue/purchase of tender is **21.05.2018** up to 3.00 PM (Generally stopped two days before the date fixed for the opening of tenders).
- 9. Earnest money amounting to <u>₹12,450.00</u> deposited at the IIT(ISM) cash counter/ Demand Draft to a Nationalised Bank in favour of "Registrar, IIT (ISM) Dhanbad." Must accompany each tender to be in a sealed cover superscribed "Tender for the above work" and addressed to Campus Engineer, IIT (ISM), Dhanbad.
- 10. The contractor whose tender is accepted will be required to furnish by way of security deposit for the due fulfillment of the contract. Such sum will amount to 10% of the total cost of works awarded.
- 11. The acceptance of a tender will rest with the Campus Engineer who does not bind himself to accept the lowest tender and reserve to himself the authority to reject any or all the tenders received without assignment of any reason. All tenders in which any of the prescribed conditions are not fulfilled or are incomplete in any respect are liable to be rejected.
- 12. Canvassing in connection with the tenders is strictly prohibited and the tenders submitted by the contractors who resort to canvassing will be liable to rejection.
- 13. An item rate tender containing percentage below/above will be summarily rejected, however a tender voluntarily offers a rebate, this may be considered.
- 14. Special care should be taken to write the rates in figures as well as in words and the amounts in figures only, in such a way that interpolation is not possible. The total amount should be written both in figures

and in words. In case of figures the word "Rs." Should be written before the figures or rupees and word "P" after the decimal figure e.g. Rs. 2.15 p and case of words the word Rupees should precede and the word "paise" should be written at the end, unless the rate is in whole rupees and followed by the word "only". It should invariably be up to two decimal places. While quoting the rate in schedule of quantities the word "only" should be written closely following the amount and it should not be written in the next line.

- 15. The Director/Registrar does not bind himself to accept the lowest or any tender and reserves to himself the right of accepting the whole or any part of the tender and the tenderer shall be bound to perform the same at the rate quoted.
- 16. All taxes except Goods & Service Tax (GST) as applicable in respect of this contract shall be payable by the contractor and IIT(ISM) will not entertain any claim whatsoever in this respect. GST will be paid along with the contractor's bill.
- 17. The tender for the work shall remain open for acceptance for a period of 90 days from the date of opening of the tender. If any tenderer withdraws his tender before the said period or makes any modification in the terms and conditions of the tender which are not acceptable to the department, then the IIT(ISM) without prejudice to any other right or remedy, be at liberty to forfeit of the said earnest money.
- 18. Rates quoted by the contractor in item rate tender in figures and words shall be accurately filled in so that there is no discrepancy in the rates written in figures and words. However, if a discrepancy is found the rates which correspond with the amount worked out by the contractor shall be taken as correct.
- 19.If the amount of an item is not worked out by the contactor or it does not correspond with the rate written either in figure or in words then the rate quoted by the contractor in words shall be taken as correct.
- 20. Where the rates quoted by the contractor in figures and in words tally but the amount is not worked out correctly, the rate quoted by the contractor will be taken as correct and not the amount.

Campus Engineer IIT(I.S.M), Dhanbad

Sul-

### INDIAN INSTITUTE OF TECHNOLOGY (ISM), DHANBAD - 826004

M/s		
Name of Work:	A/R & Maintenance work (Inside) at Topaz Hostel	

### SCHEDULE OF WORK

SI.	ITEM OF WORKS	QUANTITY	RATE	AMOUNT
No.				
1.	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in:  Cement mortar 1:6 (1 cement: 6 coarse sand)	1.00 cum		
2.	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundations and plinth in: Cement mortar 1:3 (1 cement: 3 coarse sand)	10.00 sqm		
3.	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement: 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels.  Raj Nagar Plain white marble/ Udaipur green marble/ Zebra black marble  Area of slab over 0.50 sqm	4.00 sqm		
4.	Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows, including ISI marked M.S. pressed butt hinges bright finished of required size with necessary screws, excluding panelling which will be paid for separately, all complete as per direction of Engineer-in-charge.  Kiln seasoned and chemically treated hollock Wood  30 mm thick shutters	2.00 sqm		



<ul><li>5.</li><li>6.</li></ul>	Providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or paneled and glazed shutters 25 mm to 40 mm thick:  Kiln seasoned and chemically treated hillock wood  Particle Board 12 mm thick	2.00 sqm	
	Plain particle board flat pressed, 3 layer or graded wood particle board medium density Grade I, IS: 3087 marked		
7.	Providing and fixing glazed shutters for doors, windows and clerestory windows using 4 mm thick float glass panes, including ISI marked M.S. pressed butt hinges bright finished of required size with necessary screws.  Second class teak wood 30 mm thick	2.00 sqm	
8.	Providing and fixing nickel plated M.S. pipe curtain rods with nickel plated brackets:  25 mm dia (heavy type)	30.00 mtr	
9.	Providing and fixing fly proof galvanized M.S. wire gauge to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia 0.63 mm all complete.  With 12 mm mild steel U beading	40.00 sqm	
10.	Providing and fixing ISI marked oxidised M.S. sliding door bolts with nuts and screws etc. complete: 250x16 mm	10.00 each	
11.	Providing and fixing ISI marked oxidised M.S. tower bolt black finish, (Barrel type) with necessary screws etc. complete: 200x10 mm	20.00 each	
12.	Providing and fixing ISI marked oxidised M.S. handles conforming to IS:4992 with necessary screws etc. complete: 125 mm	30.00 each	
13.	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete.  40 mm thick with 20 mm nominal size stone aggregate	16.00 sqm	

14. Providing and fixing on wall face unphasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes.  75 mm diameter  15. Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm  16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster of mix: 1:6 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer of approved brand and manufacture on real surface: Water thinnable scanner or required colour to give an even shade: Two or more coats on new work over an under coat of surface surface and manufacture or required colour to give an even shade:  Two or more coats on new work over an under coat of surfale shade with ordinary paint of approved brand and manufacture or required colour to give an even shade:  Two or more coats on new work over an under coat of surfale shade with ordinary paint of approved brand and manufacture or required colour to give an even shade:  Two or more coats on new work over an under coat of surfale shade with ordinary paint of approved brand and manufacture, over the plastered wall surface to prepare the surface even and smooth complete	14.	Providing and fixing on wall face	5.00
conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion, (1) Single socketed pipes. 75 mm diameter  15. Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  3) Single tee with door 110x110x110 mm  5) Bend 87.5° 110 mm bend  16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture.  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture; over the plastered wall surface to; over the plastered wall surface to prepare the surface even and	14.	, ,	3.00 mtr
jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes.  75 mm diameter  15. Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 1382 (leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm  16. 12 mm cement plaster of mix : 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix : 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thiunable cement primer of approved brand and manufacture on wall surface : Water thimnable cement primer of approved brand and manufacture of required colour to give an even shade : Two or more coats on new work over an under coat of surface on the coat of surface in the coat of surface in the coat of paproved brand and manufacture?  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to repeate the surface even and		,	
5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes.  75 mm diameter  15. Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm  b) Bend 87.5° 110 mm bend  16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of surface with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture over an under coat of surface is propare the surface even and			
expansion, (i) Single socketed pipes.  75 mm diameter  15. Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised figid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm  16. 12 mm cement plaster of mix: 1.36 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1.4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer of colour to give an even shade: Two or more coats on new work over an under coat of surface is me work over an under coat of surface is me work over an under coat of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of surface is me, of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of surfable shade with ordinary paint of approved brand and manufacture?  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture; over the plastered wall surface to prepare the surface even and		jointing with seal ring conforming to IS:	
15. Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm  b) Bend 87.5° 110 mm bend  16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer water thinnable cement primer of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of surface is more with coat of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture?  20. Providing and applying white cement based putty of average thickness I mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		5382, leaving 10 mm gap for thermal	
15. Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm  b) Bend 87.5° 110 mm bend  16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer water thinnable cement primer of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of surface is more with coat of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture?  20. Providing and applying white cement based putty of average thickness I mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
15. Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm   16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture of required colour to give an even shade:  19. Providing and applying white cement based putty of average thickness I mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm   16. 12 mm cement plaster of mix : 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix : 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface : Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	15		
accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm  Bend 87.5° 110 mm bend  16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture wall surface to prepare the surface even and	***	, ,	***
water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm  b) Bend 87.5° 2.00 each  16. 12 mm cement plaster of mix: 1.6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of sportoved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture wall surface to prepare the surface even and			
including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm  5.00 each 2.00 e			
to IS: 5382, leaving 10 mm gap for thermal expansion.  a) Single tee with door 110x110x110 mm  5.00 each  10 mm bend  12.00 each  12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  13.00 sqm  15.00 sqm  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture, over the plastered wall surface to prepare the surface even and			***************************************
expansion. Single tee with door 110x110x110 mm  3.00 each  10x110x110 mm  2.00 each  2.00 each  110 mm bend  12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  Water thinnable cement primer  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture; over the plastered wall surface to prepare the surface even and			
a) Single tee with door 110x110x110 mm  3.00 each  10x110x110x110 mm  2.00 each  110 mm bend  2.00 each  110 mm bend  3.00 sqm  11ch (1 cement: 6 fine sand)  12 mm cement plaster of mix: 1.ch (1 cement: 6 fine sand)  13 0.00 sqm  14 (1 cement: 4 fine sand)  15 0.00 sqm  18 Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19 Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		to IS: 5382, leaving 10 mm gap for thermal	
b) Bend 87.5° 110 mm bend  16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture, over the plastered wall surface to prepare the surface even and		expansion.	
b) Bend 87.5° 110 mm bend  16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture, over the plastered wall surface to prepare the surface even and	a)	Single tee with door	3.00 each -
b) Bend 87.5° 110 mm bend  16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture, over the plastered wall surface to prepare the surface even and		_	
16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	,,	D 107.00	
16. 12 mm cement plaster of mix: 1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	(0)		2.00 each
1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		110 mm bend	
1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
1:6 (1 cement: 6 fine sand)  17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	16.	12 mm cement plaster of mix:	30.00 sam
17. 12 mm cement plaster finished with a floating coat of neat cement of mix: 1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		*	
coat of neat cement of mix:  1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		and (a demand o mile stand)	
coat of neat cement of mix:  1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			1
coat of neat cement of mix:  1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
coat of neat cement of mix:  1:4 (1 cement: 4 fine sand)  18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	17	12 mm computator frist desire for the	5.00
18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	1/.		5.00 sqm
18. Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface:  Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		-	
primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		1:4 (1 cement: 4 fine sand)	
primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			-4
primer of approved brand and manufacture on wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	18.	Applying one coat of water thinnable cement	1200.00
wall surface: Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		44 · ·	sam
Water thinnable cement primer  19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	İ		
19. Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		mater miniatio coment printer	
approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		state & M	
approved brand and manufacture of required colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	10	Dairein and at a control of	2.00
colour to give an even shade:  Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	19.		2.00 sqm
Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
under coat of suitable shade with ordinary paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and			
paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		Two or more coats on new work over an	
paint of approved brand and manufacture  20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	anguari	under coat of suitable shade with ordinary	
20. Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and		-	
putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	and the same of th	•	
putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and	20.	Providing and applying white cement based	150 00 sam
brand and manufacturer, over the plastered wall surface to prepare the surface even and			120.00 adin
wall surface to prepare the surface even and	***************************************		
	veri de la companya d		
smooth complete	VI		
	- Account	smooth complete	

21.	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per directions of Engineer-In-Charge.  With cement mortar 1:4 (1cement: 4 coarse sand)	5.00 sqm		
22.	White washing with lime to give an even shade: Old work (two or more coats)	1000.00 sqm	-6	
23.	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	900.00 sqm		
24.	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade: Old work (one or more coats)	3300.00 sqm		
25.	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:  One or more coats on old work	300.00 sqm		
26.	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade Old work (one or more coats applied @ 0.83 ltr/10 sqm).	110.00 sqm		
27.	Cleaning of terrace/loft water storage tank (inside surface area) upto 2000 litre capacity at all heights with coconut brushes, duster etc., removal of silt, rubbish from the tank and cleaning the tank with fresh water disinfecting with bleaching powder @ 0.5gm per litre capacity of tank, including marking the date of cleaning on the side of tank body with the help of stencil and paint and disposing of malba, all complete as per direction of Engineer-in-Charge.  (The old date already written on tank should be removed with paint remover or black paint and if date is not written with the stencil or old date is not removed deduction will be made @ Rs. 0.10 per litre if during cleaning any GI fittings or ball cock is damaged that is to be repaired by contractor at his own cost and nothing extra will be paid on this account)	50,000.00 litre		

28.	Demolishing brick work manually/ by	1.00 cum		
20.	mechanical means including stacking of	1.00 Cum		
		TINA		
	· - *			W. ALIEN
	unserviceable material within 50 metres lead			
	as per direction of Engineer-in-charge			
<u></u>	In cement mortar			
29.	Taking out doors, windows and clerestory	5.00 each		
	window shutters (steel or wood) including			
	stacking-within 50 metres lead:			
	Of area 3 sq. metres and below			
	-			
30.	Disposal of building rubbish / malba / similar	3.15 cum		
	unserviceable, dismantled or waste materials			
	by mechanical means, including loading,			
	transporting, unloading to approved			V
	municipal dumping ground or as approved by		~	William
	Engineer-in-charge, beyond 50 m initial lead,		]	
31.	for all leads including all lifts involved.	1.00 1		
31.	Providing and fixing wash basin with C.I.	1.00 each		
	brackets, 15 mm C.P. brass pillar taps, 32 mm			
	C.P. brass waste of standard pattern,			
	including painting of fittings and brackets,			
	cutting and making good the walls wherever			
	require:			
	White Vitreous China Flat back wash basin		<u> </u>	
	size 550x 400 mm with single 15 mm C.P.			
	brass pillar Tap			
32.	Providing and fixing white vitreous china	1.00 each		
	water closet squatting pan (Indian type):			
	Orissa pattern W.C. pan of size 580x440 mm			
	•			
33.	Providing and fixing P.V.C. low level	5.00 each		
	flushing cistem with manually controlled	0,000 00011		
	device (handle lever) conforming to IS:			
	7231, with all fittings and fixtures complete.		-	
	10 litre capacity – White			
34.	Providing and fixing white vitreous china flat	1.00 each		
- ''	back or wall corner type lipped front urinal	1.00 Cacil		
	basin of 430x260x350 mm or 340x410x265			
	mm sizes respectively.			· ·
	min sizes respectively.		;	
1				
3.5	Providing and fiving DVC	5.001		
35.	Providing and fixing P.V.C. waste pipe for	5.00 each		
35.	sink or wash basin including P.V.C. waste	5.00 each		
35.	sink or wash basin including P.V.C. waste fittings complete.	5.00 each		
35.	sink or wash basin including P.V.C. waste fittings complete. Semi rigid pipe	5.00 each		
35.	sink or wash basin including P.V.C. waste fittings complete.	5.00 each		
	sink or wash basin including P.V.C. waste fittings complete. Semi rigid pipe 32 mm dia			,
35.	sink or wash basin including P.V.C. waste fittings complete. Semi rigid pipe 32 mm dia  Providing and fixing 600x450 mm beveled	5.00 each		
	sink or wash basin including P.V.C. waste fittings complete.  Semi rigid pipe 32 mm dia  Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved)			•
	sink or wash basin including P.V.C. waste fittings complete. Semi rigid pipe 32 mm dia  Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board			•
	sink or wash basin including P.V.C. waste fittings complete.  Semi rigid pipe 32 mm dia  Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass			
	sink or wash basin including P.V.C. waste fittings complete. Semi rigid pipe 32 mm dia  Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board			•
	sink or wash basin including P.V.C. waste fittings complete.  Semi rigid pipe 32 mm dia  Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass			•



37.	Providing and fixing PTMT towel rail complete with brackets fixed to wooden cleats with CP brass screws with concealed fittings arrangement of approved quality and colour.  600 mm long towel rail with total length of 645 mm, width 78 mm and effective height of 88 mm, weighing not less than 190 gms.  Providing and fixing PTMT 15 mm Urinal spreader size 95x69x100 mm with 1/2" BSP thread and shapes, weighing not less than 60 gms.	
39.	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge.  INTERNAL WORK - EXPOSED ON WALL 20 mm nominal outer dia Pipes	2.00 mtr
b)	25 mm nominal outer dia Pipes	3.00 mtr
c)	32 mm nominal outer dia Pipes	5.00 mtr
40.	Providing and fixing G.I. pipes complete with G.I. fittings and clamps, i/c cutting and making good the walls etc. INTERNAL WORK - EXPOSED ON WALL  15 mm dia nominal bore	1.00 mtr
	15 mm dia nommai 6016	1.00 IIII
b)	20 mm dia nominal bore	2.00 mtr
c)	25 mm dia nominal bore	2.00 mtr
41.	Making connection of G.I. distribution branch with G.I. main of following sizes by providing and fixing tee, including cutting and threading the pipe etc. complete:  25 to 40 mm nominal bore	3.00 each

42.	Providing and fixing brass stop cock of approved quality: 15 mm nominal bore	3.00 each		
43.	Providing and fixing uplasticised PVC connection pipe with brass unions: 30 cm length 15 mm nominal bore	3.00 each		
44.	Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931.  15 mm nominal bore	ŧ I		
45.	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 15mm nominal bore	2.00 each		
46.	Providing and fixing PTMT bib cock of approved quality and colour.  15mm nominal bore, 86 mm long, weighing not less than 88 gms	6.00 each		
47.	Providing and fixing PTMT pillar cock of approved quality and colour 15 mm nominal bore, 125 mm long foam flow weighing not less than 120 gms	6.00 each		
48.	Providing and fixing PTMT, push cock of approved quality and colour.  15 mm nominal bore, 98 mm long, weighing not less than 75 gms	2.00 each	-	
49.	Providing and fixing PTMT grating of approved quality and colour. Circular type 100 mm nominal dia	5.00 each	**************************************	
50.	Providing and fixing PTMT Ball cock of approved quality, colour and make complete with Epoxy coated aluminium rod with L.P./H.P.H.D. plastic ball.  25 mm nominal bore, 152mm long, weighing not less than 440 gms	6.00 each		
51.	Providing and fixing PTMT angle stop cock 15 mm nominal bore, weighing not less than 85 gms	3.00 each		

52.	Providing and fixing PTMT swivelling shower, 15 mm nominal bore, weighing not less than 40 Gms	5.00 each		
53.	Providing and fixing unplasticised P.V.C. connection pipe with PTMT Nuts, collar and bush of approved quality and colour.  15 mm nominal bore with 30cm length	4.00 each		
54.	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of Engineer-incharge. (Cost of aluminium snap beading shall be paid in basic item):  With float glass panes of 5.50 mm thickness	2.00 sqm	- ruin	
55.	Providing and fixing aluminium tubular handle bar 32 mm outer dia, 3.0 mm thick & 2100 mm long with SS screws etc .complete as per direction of Engineer-in-Charge.  Anodized (AC 15) aluminium tubular handle bar	5.00 each		
56.	Grading roof for water proofing treatment with Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	0.5 cum		
57.	Providing and laying APP (Atactic Polypropylene Polymer) modified prefabricated five layer 3 mm thick water proofing membrane, black finished reinforced with non-woven polyester matt consisting of a coat of bitumen primer for bitumen membrane @ 0.40 litre/sqm by the same membrane manufacture of density at 25°C, 0.87-0.89 kg/ litre and viscocity 70-160 cps. Over the primer coat the layer of membrane shall be laid using Butane Torch and sealing all joints etc, and preparing the surface complete. The vital physical and chemical parameters of the membrane shall be as under: Joint strength in longitudinal and transverse direction at 23°C as 650/ 450N/5cm. Tear strength in longitudinal and transverse direction as 300/250N. Softening point of membrane not less than 150°C. Cold flexibility shall be upto -2°C when tested in accordance with ASTM, D - 5147. The laying of membrane shall be got done through the authorised applicator of the manufacturer of membrane:  3 mm thick	2.00 sqm		

<ul> <li>Supplying, assembling, lowering and fixing in vertical position in bore well unplasticized PVC medium well screen (RMS) pipes with ribs, conforming to IS: 12818, including hire &amp; labour charges, fittings &amp; accessories etc. all complete, for all depths, as per direction of Engineer-in-charge.</li> <li>150 mm nominal size dia</li> <li>Proving and fixing 30 mm thick consisting of frame made out of tubes of 19 gauge thickness size of 20 mm x 40 mm of stiles as well as top, bottom &amp; lock rail, M.S. frame shall have coat of metal primer of approved and manufacturer. The inside panels shall consist of 20 mm thick multi chamber hollow PVC section of 1 mm wall thickness, bounded using solvents cynoacrylate adhesive with 5 mm (+ 0.25) thick plain/PVC sheet of density 600 kg/ CBM manufactured by an ISO-0901-2008 certified company on side of the inside panel. All the four edge of the panel to be sealed with lipping of 10 mm thick and 20 mm wide PVC sheet baton (made by sticking 2 nos sheets of 5 mm (+ 0.25) thickness using PVC solvent cement adhesive. Door as liping to be painted with PVC ink of matching colour of plain/prelam moul PVC sheet of door 20 mm thick (5 mm x 4 nos) thick PVC sheet to be give for lock provision at lock height. Door to be fixed with frame with 3 nos stair steel butt hinges of size 100 mm *25 mm *2 mm and 50 mm long steel screws direlled suitable to pass through both the walls of the M.S. tube other hard should be fixed with 25 mm *8 mm size steel screws tec, complete as per direction of Engineer-in-charge, manufacturers specification and drawing.</li> <li>60. P/F M.S door ring with necessary screw nails etc.</li> <li>62. P/F M.S door door edge by chelling the existing wooden door shutter / cup board shutter etc complete.</li> <li>63. P/F M.S door ning with necessary screw nails etc.</li> </ul>	[ 60		F 00	I	T
& labour charges, fittings & accessories etc. all complete, for all depths, as per direction of Engineer-in-charge.  150 mm nominal size dia  59. Proving and fixing 30 mm thick consisting of frame made out of tubes of 19 gauge thickness size of 20 mm x 40 mm of stiles as well as top, bottom & lock rail, M.S. frame shall have coat of metal primer of approved and manufacturer. The inside panels shall consist of 20 mm thick multi chamber hollow PVC section of 1 mm wall thickness, bounded using solvents cynoacrylate adhesive with 5 mm (+ 0.25) thick plain/PVC sheet of density 600 kg/ CBM manufactured by an ISO-9001-2008 certified company on side of the inside panel. All the four edge of the panel to be sealed with lipping of 10 mm thick and 20 mm wide PVC sheet baton (made by sticking 2 nos sheets of 5 mm (+ 0.25) thickness using PVC solvent cement adhesive. Door as liping to be painted with PVC ink of matching colour of plain/prelam moul PVC sheet of door 20 mm thick (5 mm x 4 nos) thick PVC sheet to be give for lock provision at lock height. Door to be fixed with frame with 3 nos stair steel butt hinges of size 100 mm *25 mm *2 mm and 50 mm long steel screws etc., complete as per direction of Engineer-in-charge, manufacturers specification and drawing.  60. P/F M.S door ring with necessary screw nails the existing wooden door shutter / cup board shutter etc complete.	38.	vertical position in bore well unplasticized PVC medium well screen (RMS) pipes with	5.00 mtr		
59. Proving and fixing 30 mm thick consisting of frame made out of tubes of 19 gauge thickness size of 20 mm x 40 mm of stiles as well as top, bottom & lock rail, M.S. frame shall have coat of metal primer of approved and manufacturer. The inside panels shall consist of 20 mm thick multi chamber hollow PVC section of 1 mm wall thickness, bounded using solvents cynoacrylate adhesive with 5 mm (+ 0.25) thick plain/PVC sheet of density 600 kg/ CBM manufactured by an ISO-9001-2008 certified company on side of the inside panel. All the four edge of the panel to be sealed with lipping of 10 mm thick and 20 mm wide PVC sheet baton (made by sticking 2 nos sheets of 5 mm (+ 0.25) thickness using PVC solvent cement adhesive. Door as liping to be painted with PVC ink of matching colour of plain/prelam moul PVC sheet of door 20 mm thick (5 mm x 4 nos) thick PVC sheet to be give for lock provision at lock height. Door to be fixed with frame with 3 nos stair steel but thinges of size 100 mm *25 mm *25 mm *25 mm *35		& labour charges, fittings & accessories etc.			
frame made out of tubes of 19 gauge thickness size of 20 mm x 40 mm of stiles as well as top, bottom & lock rail, M.S. frame shall have coat of metal primer of approved and manufacturer. The inside panels shall consist of 20 mm thick multi chamber hollow PVC section of 1 mm wall thickness, bounded using solvents cynoacrylate adhesive with 5 mm (+ 0.25) thick plain/PVC sheet of density 600 kg/ CBM manufactured by an ISO-9001-2008 certified company on side of the inside panel. All the four edge of the panel to be sealed with lipping of 10 mm thick and 20 mm wide PVC sheet baton (made by sticking 2 nos sheets of 5 mm (+ 0.25) thickness using PVC solvent cement adhesive. Door as liping to be painted with PVC ink of matching colour of plain/prelam moul PVC sheet of door 20 mm thick (5 mm x 4 nos) thick PVC sheet to be give for lock provision at lock height. Door to be fixed with frame with 3 nos stair steel butt hinges of size 100 mm *25 mm *2 mm and 50 mm long steel screws drilled suitable to pass through both the walls of the M.S. tube other hard should be fixed with 25 mm *8 mm size steel screws etc, complete as per direction of Engineer-in-charge, manufacturers specification and drawing.  60. P/F M.S door ring with necessary screw nails etc.  61. Repairing the wooden door edge by chelling the existing wooden door shutter / cup board shutter etc complete.		150 mm nominal size dia			
(made by sticking 2 nos sheets of 5 mm (+ 0.25) thickness using PVC solvent cement adhesive. Door as liping to be painted with PVC ink of matching colour of plain/prelam moul PVC sheet of door 20 mm thick (5 mm x 4 nos) thick PVC sheet to be give for lock provision at lock height. Door to be fixed with frame with 3 nos stair steel butt hinges of size 100 mm *25 mm *2 mm and 50 mm long steel screws drilled suitable to pass through both the walls of the M.S. tube other hard should be fixed with 25 mm *8 mm size steel screws etc, complete as per direction of Engineer-in-charge, manufacturers specification and drawing.  60. P/F M.S door ring with necessary screw nails etc.  61. Repairing the wooden door edge by chelling the existing wooden door shutter / cup board shutter etc complete.	59.	frame made out of tubes of 19 gauge thickness size of 20 mm x 40 mm of stiles as well as top, bottom & lock rail, M.S. frame shall have coat of metal primer of approved and manufacturer. The inside panels shall consist of 20 mm thick multi chamber hollow PVC section of 1 mm wall thickness, bounded using solvents cynoacrylate adhesive with 5 mm (+ 0.25) thick plain/PVC sheet of density 600 kg/ CBM manufactured by an ISO-9001-2008 certified company on side of the inside panel. All the four edge of the	10.00 sqm		
61. Repairing the wooden door edge by chelling the existing wooden door shutter / cup board shutter etc complete.  62. P/F M.S altras for wooden cup board shutter 30.00 each		thick and 20 mm wide PVC sheet baton (made by sticking 2 nos sheets of 5 mm (+ 0.25) thickness using PVC solvent cement adhesive. Door as liping to be painted with PVC ink of matching colour of plain/prelam moul PVC sheet of door 20 mm thick (5 mm x 4 nos) thick PVC sheet to be give for lock provision at lock height. Door to be fixed with frame with 3 nos stair steel butt hinges of size 100 mm *25 mm *2 mm and 50 mm long steel screws drilled suitable to pass through both the walls of the M.S. tube other hard should be fixed with 25 mm *8 mm size steel screws etc, complete as per direction of Engineer-in-charge, manufacturers specification and drawing.		**	
the existing wooden door shutter / cup board shutter etc complete.  62. P/F M.S altras for wooden cup board shutter 30.00 each	60.	P/F M.S door ring with necessary screw nails	30.00 each		
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		the existing wooden door shutter / cup board	120.00 mtr		
	62.	· -	30.00 each		

63.	Necessary repair for old loose kundi, nuts, door blot hook etc for door, window & cup board shutter in rooms by using carpenter /labour etc. complete one job for each block	2.00 each block	
64.	Necessary welding work for fixing of old loose cupboard /door shutter in inside room /wash room etc.	10.00 each	
65.	Repair of old MS glaze window shutter leaf by welding new additional 2 nos moveable M.S hinge for one single leaf including necessary scaffolding complete.	6.00 each	 a had not do the
66.	Grinding and polishing with necessary chemicals, oxalic powder fine sand where ever required etc on kota stone mosaic marbel flooring as directed by Engg. in charge	650.00 sqm	
67.	Renewing acrylic seat with putty and nails wherever necessary including racking out the old putty.  Providing & fixing 4 mm thick acrylic seat at windows with necessary new putting, Z pin etc as required and as per deduction of Engineer-in-charge.	15.00 sqm	
68.	Providing & commode seat cover (PVC) hind ware or its equivalent	1.00 each	
69.	P/F long size flat back large hindware or equivalent make white urinals (39x37.5x59)cm	1.00 each	
70.	Cleaning of chocked sewer line and partial desilting of the same & dechocking of sewer lines. Dechocking and flushing of sewer line by Soap, brush, cloths etc complete excluding the cost of scaffolding	30.00 mtr	
71. a)	'SCUD gold " Gun Metal Gate Valves (Hattersley Type) Non rising steam having solid forged wedge with teflon gland packing 25 mm nominal bore	2.00 each	
b)	20 mm nominal bore	1.00 each	

Sal.

72	P/F PVC water tank cover for 1000 lit	5.00 each
	ika s	
	,	
73.	P/F PVC water tank cover for 2000 lit	3.00 each
		-
74.	Repairing of PVC cistern by replacement of	20.00 each
/ 1.	necessary fittings like handle, syphon etc	20.00 cach
	Complete	
7.5	D :11 0 C : CY :	
75.	Providing & fixing G.I pipes complete with G.I fittings including cutting & making good	
	the wall	
a)	15 mm dia nominal bore	2.00 mtr
b)	20 mm dia nominal bore	5.00 mtr
76.	Providing & Fixing connection pipe heavy	6.00 each
	duty for geyser	
77.	Applying water proofing compound L.W plus	2.00 kg
	reprinted the proofing compound 2.11 plus	2.00 Kg
	1	
78.	Negociami Coeffoldina for annual setting	5.001
70.	Necessary Scaffolding for grove cutting racking out of joints cleaning the garbage for	5.00 each
	repair the drain mouth at toilet.	
		**
70	Classica Silva Sil	200
79.	Clearing, oiling of the existing collapsible gate for smooth run of the same etc. complete	2.00 each
	Same for smooth run of the same etc. complete	
	, v .	
	- ··	

TOTAL - ₹

( Rupees in word	
i i	
	Saralh
SIGNATURE OF CONTRACTOR	Campus Enginee

Campus Engineer IIT (I.S.M), DHANBAD

ole gy

CM-4



# INDIAN INSTITUTE OF TECHNOLOGY (1.S.M.), DHANBAD - 826004

(CAMPUS MAINTENANCE UNIT)

### TERMS & CONDITIONS OF CONTRACTOR FOR WORKS

### General Rules and Directions:

 All works proposed for execution by contractor will be notified in a form of invitation to tender on Notice Board/Paper advertisements and signed by the Campus Engineer/Asstt. Campus Engineer.

This form will state the work to be carried out as well as the date for submitting and opening tenders and the time allowed for carrying out the work, also the amount of earnest money to be deposited with the tender, and the percentage at which the Security Deposit shall be deducted from the bills of the successful tenderer. Copies of the Specifications, designs and drawing and the schedule of quantities and of rates on the various descriptions of work and any other documents required in connection with the work signed for the purpose of identification by the Campus Engineer/Asstt. Campus Engineer shall also be opened for inspection by the contractor of the office of the Campus Engineer/Asstt. Campus Engineer during office hours.

- 2. In the event of the tender being submitted by a firm it must be signed separately by each partner thereof or in the event of the absence of any partner it must be signed on his behalf by a person holding a power of attorney authorized him to do so, such power of attorney to be produced with the tender and it must disclose that the firm is duly registered under the Indian Partnership Act.
- 3. Receipt for payments made on account of work when executed by a firm must also be signed by the several partner except where the contractors are described in their tender as a firm which case the receipts must be signed in the name of the firm by one of the partners on some other person; having authority to give effectual receipt for the firm.
- 4. Any person who submits a tender shall fill up the usual printed from stating at what rate he is willing to undertake each item of the work. Tender which proposes any alternation in the work specified in the said form of invitation; to the tender or in the time allowed by carrying out the work or which contain any other conditions of any sort will be liable to rejection. No single tender shall include more than one work but contractors who wish to tender for two or more works shall submit a separate tender for each. Tenders shall have the name and number of the work to which they refer written outside the envelope.
- 4A. The rate(s) and/or amount(s) must be quoted in decimal coinage.
- The Campus Engineer/Asstt. Campus Engineer representative of RG/DT and from account section will open tenders in the presence of any intending contractors who may be present at the time of opening the tender.
- The officer inviting tenders shall have the right of rejecting all or any of the tenders will not be bound to accept the lowest tender.
- 7. The receipt of an accountant or clerk for any money paid by the contractor will not be considered as any acknowledgement of payment to the Campus Engineer/Asstt. Campus Engineer and the contractor shall be responsible for seeing that he procures a receipt signed by the duly authorized cashier of I.I.T. (I.S.M.).
- 8. The memorandum of work tendered for and the schedule of materials to be supplied by the Indian School of Mines, and their issue rates shall be filled in; and completed in the office of the Campus Engineer/Asstt. Campus Engineer before the tender form issued to an intending tenderer without having been so filled in and completed the shall request the office to have this done before he completes and delivers his tender.
- The tenderers shall sign a declaration under the official Secret Act. for maintaining secrecy of the tender documents drawing of other records connected with the work given to them, the unsuccessful tenderers shall return all the drawing given to them.

### **DECLARATION**

I/We hereby declare that I/We shall freat the tender documents drawings and the records connected with the work as secret/confidential documents and shall not communicate information derived there from to any person other than a person to whom I/We am/are authorized to communicate the same or use the information in any manner prejudice to the safety of the Indian Institute of Technology (Indian School of Mines).

item F	Rate Tender for works in s as well as in words		C	ONTRACTOR'S SIGNATURE
thereir	n, and the accordance	execution for the Director, Indian tan amount of E	ed in such memo	randum at the rates specified
for, by	and in all respects in ac	nd in clause 11 of the conditions of c cordance with such conditions so fa	ontract and with s ras applicable.	such materials as one provided
Memo	c) Earnest mone d) Security Depo i) 10% of the ter The security deposit mentioned above and security deposit. e) Time allowed month(s) Should this te the terms and provis contained in notice inv Director, I.I.T. (I.S.M.) sum of E Scheduled Bank guan the work specified in the shall without prejudice absolutely, otherwise mentioned against clar to in the tender docume such deviations as ma deviation limit of tende	st callations, water supply & drainage ck ey cosited indered value of the work will be ded will be collected by deduction from the earnest money if deposited in ca for the work from the day after the d days inder be accepted in whole or in par ions of the said conditions anner ions of the said conditions anner ions of the said renders, so far as applicable a or his successors in office the sur anteed by the Reserve Bank of Ind anteed by	the running bills ash at the time of attemption at the time of attemption at the time of attemption at the time at the said Direct at liberty too for e retained by himorandum; (ii) to for (iii) to (iffty) percent is the tender down at the time at the said by himorandum; (ii) to for the time at	ref the contractor of the rates tender will be treated as part of the reto commence
	Address	Occupation		Signature of the Contractor

### CONDITIONS OF CONTRACT

### Definitions.

3115

1) The 'Contract' means the documents forming the tender and acceptance thereof and the formal agreement executed between the Registrar I.I.T. (I.S.M.) and the Contractor together with the documents referred to therein including these conditions, the specifications, designs, drawings and instructions issued from time to time by the Engineer in charge and all these documents taken together shall be deemed to from on econtract and shall be complementary to on another.

2) In the contract the following expression shall unless the contract otherwise requires, have the

meaning hereby respectively assigned to them.

a) The expression "Work" or Works shall unless there be something either in the subject or context. repugnant to such construction be constructed and taken to mean the works by or by virtue of the contract contracted to be executed whether temporary or permanent and whether original, altered, substituted or additional.

b) The 'Site" Shall mean the land and or other places on into or through which "Work" is to be executed under the contract or any adjacent land, path or street through which work is to be executed under the contract or any adjacent land, path or street which may be allotted or used for the purpose or carrying out the contract.

c) The 'Contractor' shall mean the individual or firm or company whether incorporated or not undertaking the works and shall include the legal personal representative or such individual or the persons composing such firm or company or the successors or such firm or company and the permitted assigns of such individual or firm of firms of company.

d) The Director means the Director, Indian Institute of Technology (Indian School of Mines).

e) i.l.T. (I.S.M.) or Indian Institute of Technology (Indian School of Mines) shall mean the Registrar Indian Institute of Technology (Indian School of Mines).

f) The term Registrar includes Registrar, Indian Institute of Technology (Indian School of Mines) and who shall sign agreement on behalf of the School.

work and who shall sign and other documents connected with contract work on behalf of School. Words imparting the singular number include the plural number and vice versa.

### Security Deposit:

CLAUSE-1:

The person/persons whose tender(s) may be accepted (hereinafter called the contractor) shall permit ISM at the time of making any payment of him for work done under the contract to deduct such sum as along with the sum already deposited as earnest money will amount 10% of the tendered value of the work.

Such deductions will be held by I.I.T. (I.S.M.) by way of security deposit. Provided always that the I.I.T. (I.S.M.) for this purpose shall be entitled to recover 10% percent the amount of each running bill till the balance of the amount of Security deposit is realized.

### Compensation for delay: CLAUSE 2:

The time allowed for carrying out the work as entered in the tender shall be strictly observed by the contractor for and shall be deemed to be of the essence of the contract on the part of the contractor and shall be reckoned from the tenth day after the date on which the order to commence the work is issued to the contractor. The work shall throughout the stipulated period of the contract be proceeded with all due diligence and the contractor shall pay as compensation and amount equal to one percent per day or such smaller amount as the Campus Engineer/Asstt. Campus Engineer (Whose decision in wiring shall be final) may decide on the amount of the tendered cost of the whole work as shown in the tender for every day that the work remains uncommented or unfinished after the proper dates and further to ensure good progress during the execution of the work. The contractor shall be bound in all cases in which the time allowed for any work (save for special jobs) to complete one eighth of the whole of the work before one fourth of the whole time allowed under the contract has elapsed three-eights of the work, before one-half of such time has elapsed, the three-eights of the work before one-half of fourths of such time has elapsed. However for special jobs if a time schedule has been submitted by the contractor and the same has been accepted by Engineer-incharge the contractor shall comply with the said time schedule.

In the event of the contractor failing to comply with condition be shall be liable to pay as compensation an amount an amount equal to one percent or such smaller amount as the Campus Engineer/Asst. Campus Engineer (Whose decision in writing shall be final) may decide on the said tendered cost of the whole work for everyday the due quantity of work remains incomplete. Provided always that the entire amount of compensation to be paid under the provisions of the clause shall not exceed ten percent on the tendered cost of the work as shown in the tender.

### CLAUSE 3:

fie.

cofer Tia

The Campus Engineer/Asstt. Campus Engineer may without prejudice to his right against the contract in respect or any delay inferior work man ship or otherwise or to any claims for damage in respect of any breaches of the contract and without prejudice to any rights of remedies under the any of the provisions of this contract or otherwise and whether the date for completion has or has not elapsed by notice in writing absolutely determine the contract in any of the following cased:

i) If the contractor having been given by the Campus Engineer/Asstt. Campus Engineer a notice in writing to rectify, reconstruct or replace any defective work or that the work is being performed in any inefficient otherwise improper or unworkman like manner shall omit to comply with the requirements of such notice for a period of seven days there after or if one contractor shall delay or suspended the execution of the work so that either in the judgement of the campus engineer (which shall be final and binding) he will be unable to secure completion of the work, by the date for completion or he has already failed to complete the work by that date;

ii) If the contractor being a company shall pass a resolution or the court shall make an order that the company shall be wound up or if a receiver or a manager on behalf or a creditor shall be appointed or if circumstances shall arise which entitle the court of creditor to appoint a receiver a manager or which entitle the court to make a winding up order;

iii) If the contractor commits breach of any of the terms and conditions of this contract;

iv) If the contractor commits any acts mentioned in clause 18 thereof. When the contractor has made himself liable for action under any of the cases aforesaid, the Campus Engineer/Asstt. Campus Engineer on behalf of the Director Indian Institute of Technology (Indian School of Mines) shall have powers;

- a) To determine or rescind the contract as aforesaid (of which termination or recession notice in writing to the contractor under the hand of the Engineer-in-Charge shall be conclusive evidence). Upon such determination of rescission the security deposit of the contractor shall be liable to forfeit and shall be absolutely at the disposal of ISM.
- b) To employ labour paid by the I.I.T. (I.S.M.) and to supply material to carry out the work or any part of the work debiting the contractor with the cost of the labour and the price of the materials (of the amount of which cost and price certified by the Engineer-in-charge shall be final and conclusive against the Contractor) and crediting him with the value of the work done in all respects in the same manner and at the same rates as if it has been carried out by the contractor under the same terms of his contract certificate of the Campus Engineer/Assit. Campus Engineer as to the value of the work done shall be final and conclusive against the contractor, provided always that action under the sub-caluse shall only be taken after giving notice in writing to the contractor. Provided also that if the expenses incurred by the department are less than the amount payable to the contractor at his agreement rates, the difference should not be paid to the contractor.
- c) After giving notice in the contractor to measure up the work of the contractor and to take such part thereof as shall be unexecuted out of his hands and to give it to another contractor to complete in which case any expenses which may be incurred in excess of the sum which would have been paid to the original contractor in the whole work has been executed by him (of the amount of which excess the certificate in writing of the Engineer-in-Charge shall be final and conclusive, shall be borne and paid by the original contractor and may be deducted from any money due to him by I.I.T. (I.S.M.) under this contract or an any other account whatsoever or from his security deposit.

In the event of any one or more of the above courses being adopted by the Engineer-in-charge the contractor shall have no claim to compensation for any loss sustained by him by reason of his having purchased or procured any materials or entered into any engagements or made any advances on account or with a view to the execution of the work or the performance of the contract. And in case action is taken under any of the provision aforesaid, the contractor shall not be entitled to recover or be paid any sum for any work thereto for actually performed under this contract unless and until the Engineeer-in-charge has certified in writing the performance of such work and the value payable in respect there of and be shall only be entitle to be paid the value so certified.

Contractor to remain liable to pay compensation in action not taken under clause 3 Powers to take possession of or require removal of or sell contractor's plant.

### CLAUSE - 4

prec the

oren

In any case in which any on the powers conferred upon the Engineer-in-charge by clause 3 thereof shall have become exercisable and the same shall not be exercised, the non exercise thereof shall not constitute a waiver of any of the conditions thereof and such powers shall not with standing be exercisable in the event of any future case of defaulty by the contractor and the liability of the contractor for compensation shall remain unaffected. In the event of the Engineer-in-charge putting in force all or any or the powers vested in him under the preceding clause he may, if he so desires after giving a notice in writing to the contractor take possession of or at the sole discretion of the Engineer-in-charge which shall be final or any tools, plant, materials and stores, in or upon the works or the site thereof belonging to the contractor or procured by the contractor and intended to be used for the case of these not being applicable at current market rates to be certified by the Engineer-in-charge whose certificate thereof shall be final otherwise Engineer-in-charge by notice in writing may order the contractor or his clerk of the works foreman or other authorized agent to remove such tools, plant materials or stores from the premises (with a time to be specified in such notice) and in the event of the contractor failing to comply with any such requisition the Engineer-in-charge may remove them at the contractor's expenses of sell them by auction or private sale on account of the contractor and at his risk in respect and the certificate of the Engineer-in-charge as to the expenses of any such removal and the amount of the proceeds and expenses of such sale shall be final and conclusive against the contractor.

# EXTENSION OF TIME: CLAUSE 5:

If the Contractor shall desire an extension of time for completion of the work on the grounds of his having been unavoidably hindered in its execution or on any other ground, he shall apply in writing to Engineer-in-charge of the date of hindrance on account of which he desires such extension as aforesaid and the Engineer-in-charge shall, if in his opinion (which shall be final) reasonable grounds be shown therefore authorize such extension of time if any, as may, in his opinion be necessary or proper.

## Completion Certificate: CLAUSE 6:

Within ten days the completion of the work, the contractor shall give notice of such completion to the Engineer-in-charge and the receipt of such notice the Engineer-in-charge shall inspect the work, and if there is no defect in the work shall furnish the contractor with a certificate of completion otherwise a provisional certificate of completion indicating defects (a) to be rectified by the contractor and/or (b) for which payment will be made at reduced rates, shall be issued but no certificate of completion, provisional or otherwise, shall be issued, nor shall the work be considered to be complete until the contractor shall have removed from the premises on which the work shall be executed all scaffolding, surplus materials rubbish and all huts and sanitary arrangements required for his/their work people on the site in connection with the execution of the work as shall have been erected of constructed by the contractor(s) and cleaned off the dirt from all wood work, doors windows walls floors or other parts of any building in upon, or about which the work is to be executed or of which he may have had possession for the purpose of the execution thereof and not until the work shall have been measured by the Engineer-incharge. If the contractor shall fail to comply with the requirements of this clause as to removal of scaffolding, surplus materials and rubbish and all huts and sanitary arrangements as aforesaid and cleaning off dirt on or before the date fixed for the completion of the work, the Engineer-in-charge may at the expense of the contractor remove such scaffolding, surplus materials and rubbish etc. and dispose of the same as he thinks fit and clean off such dirt as aforesaid, and the contractor shall have no claim in respect of any such scaffolding or surplus materials as aforesaid except for any sum actually realised by the sale thereof.

#### CLAUSE-6A

When the annual repairs and maintenance of works is carried out, the splashes and droppings from white washing, colour washing, painting etc. on walls, floors, doors, windows, etc., shall be removed and the surface gleaned simultaneously with the completion of these items of work in the individual rooms quarters or premises atc. Where the work is done without waiting for the actual completion of all the other items of work in the contract. In case the contractor fails to comply with the requirements of this clause the Engineer-in-charge shall have the gright to get this done at the cost of the contractor either departmentally or through agency. Before taking such action, the Engineer-in-charge shall give ten days notice in writing to the contractor.

CLAUSE: Deleted.

### CLAUSE 8:

Before taking any measurement of any work as has been referred to Clause 6, 7 and 8 thereof, the Engineer-in-charge or a subordinate disputed by him shall give reasonable notice to the contractor if the contractor fails to attend at the measurements after such notice or fails to countersign or to record the difference within a week from the date of measurements in the manner required by the Engineer-in-charge then in any such event the measurements taken by the Engineer-in-charge or by the subordinate deputed by him as the case may be shall be final and binding on the contractor and the contractor shall have no right to dispute the same.

### CLAUSE 9:

The Engineer-in-charge shall have full powers to require the removal from the premises of all materials which in his opinion not are in accordance with the specifications and in case of default the Engineer-in-charge shall be at liberty to employ other persons to remove the same without being answerable or accountable for any loss or damage that may happen or arise to such materials. The Engineer-in-charge shall also have full powers to require other proper materials to be substituted thereof and in case of default the Engineer-in-charge may cause the same to be supplied and all costs which may attend such removal and substitution are to be borne by the contractor.

### CLAUSE 10:

The contractor on signing an indenture in the form to be specified by the Engineer-in-charge shall be entitled to be paid during the progress of the execution of the work upto 75% of the tender value of any materials which are in the opinion of the Engineer-in-charge non perishable and are in accordance with the contract and which have been brought on the site in connection there with and are adequately stored and/or protected against damage by weather or other causes but which have not at the time of advance has been made under this subclause are incorporated in the work the amount of such advance shall be deducted from the next payment made under any of the clause or clauses of this contract.

### CLAUSE 10A:

The contractor shall treat shall all materials obtained during dismantling of a structure, excavation of the site for a work etc. as I.I.T. (I.S.M.) property and such materials shall be disposed of to the best advantage of I.I.T. (I.S.M.) according to the instruction in writing issued by the Engineer-in-charge.

### CLAUSE 11:

The contractor shall execute the whole and every part of the work in the most substantial and workman blike manner and both as regards materials and otherwise in every respect in strict accordance with the specifications. The contractor shall also confirm exactly fully and faithfully to the designs, drawings and instructions in writing in respect of the work signed by the Engineer-in-charge and the contractor shall be furnished free of charge one copy of the specifications, such designs, drawings and instructions as are not included in the "Specifications for works" in force from time to time or any other printed publication on General Specification referred to elsewhere in the contract.

# Alternation in Specifications and Designs CLAUSE 12:

012

36.10

0888

The Engineer-in-charge shall have power to make any alternation in omissions from additions to or substitution for, the original specifications that may appear to him to be necessary during the progress of the work and the contractor shall carry out the work in accordance with any instructions which may be given to him to writing by the Engineer-in-charge and such alterations omissions additions or substitutions shall not invalidate the contract and any altered, additional or substituted work which the contractor may be directed to do in the manner above specified as part of the work shall be carried out by the contractor on the same conditions in all respects on which he agreed to do the main work. The time for the completion of the work shall be extended in the proportion that the altered, additional or substituted work bears to the original contract work and the certificate of the Engineer-in-charge shall be conclusive as to such proportion over & above this a further period to the extend of 25% such extension shall be allowed to the contractor.

# Action and Compensation payable in case of bad work CLAUSE - 13:

If it shall appear to the Engineer-in-incharge or his subordinate in charge of the work that any work has been executed with unsound. Imperfect or unskillful workmanship or with materials of any inferior description or that any materials or articles provided by him for the execution of the work are unsound or of a quality inferior to that contracted for or otherwise not a accordance with the contract, the contractor shall on demand in writing which shall be made within six months of the completion of the work from the Engineer-in-charge specifying the work, materials or articles complained of notwithstanding that the same may have been passed, certified and paid for, forthwith rectify or remove and reconstruct the work so specified in whole or in part as the case may require or as the case may be remove the materials or articles so specified and provide other proper and suitable materials or articles at his own proper change and cost and in the event of his failing to do so within a period to be specified by the Engineer-in-charge in his demand aforesaid then the contractor shall be liable to pay compensation at the rate of one percent on the tendered amount for every day not exceeding ten days while his failure to do so shall continue and in the case of any such failure, the Engineer-in-charge may rectify or remove and re-execute the work or remove and replace with others, the materials or articles complained or as the case may be at the risk and expense in all respects of the contractor.

# Works to be open to inspection CLAUSE 14:

All work under or in course of execution or executed in pursuance of the contract shall at all times be open to the inspection and supervision of the Engineer-in-charge and his authorized subordinates, and the contractor shall at all times during the usual working hours, and at all other times at which reasonable notice of the intention of the Engineer-in-charge or his subordinate to visit the works shall have been given to the contractor, or either himself be present to receive order and instructions or have a responsible agent dully accredited in writing present for that purpose. Orders given to the contractor's agent shall be considered to have the same force as if they had been given to the contractor himself. The work during its progress can also be inspected by the Director/Registrar.

### Notice to be given before work is covered up CLAUSE 15:

The contractor shall give notice in writing to the Engineer-in-charge of the work before covering up or otherwise placing beyond the reach of measurement any work in order the at the same may be measured and correct dimension thereof taken before the same is so covered up or place beyond the reach of measurement and shall not cover up and place beyond the reach of measurement, any work without the consent in writing of the Engineer-in-charge or his authorized subordinate in charge of the work and the Engineer-in-charge of his authorized subordinate the work in charge shall within the aforesaid work and if any work shall be covered up or placed beyond the reach of measurement without such notice having been of the Engineer-in-charge consent being obtained the same shall be uncovered at the contractor's expense or in default thereof no payment or allowance shall be made for the such work such of the materials with which the same was executed.

Contractor liable for damage done and for imperfections noticed within the prescribed maintenance period after the certificate.

#### CLAUSE 16:

If the contractor of his working people or servants shall break deface, injure or destroy part of building in which they may be working, or any building, road, road curb, fence, enclosure, water pipe, cables, drains, electric or telephone post or wires, trees, grass or grass land, or cultivated ground contiguous to the premises on which the work or any part of it is being executed, or if any damage shall happen to the work while in progress from any cause whatever or if any defect, shrinkage or other faults appear in the work after a certificate final or otherwise of its completion shall have been given by the Engineer-in-charge as aforesaid arising out of defective or improper materials or workmanship the contractor shall upon a receipt of a notice in writing on that behalf make the same good at his own expenses or in default the Engineer-in-charge may cause the same to be made good by other workman and deduct the expense from any sums that may be then or at any time thereafter became due to the contractor or from security deposit. The security deposits of the contractor except the portion pertaining to asphaltic work.

# Contractor to supply all plant, ladders, scaffoldings etc. CLAUSE 17:

The contractor shall provide at his own cost all materials (except such special materials, if any as may in accordance with the contract be supplied from the Engineer-in-charge's stores) plant tools appliances, implements, ladders, cordage, tackle, scaffolding and temporary works requisite or proper for the proper execution of the work, whether original, altered or substituted and whether included in the specification or other documents forming part of the contract or referred to in these conditions or not, or which may be necessary for the purpose of satisfying or complying with the requirements of the Engineer-in-charge as to any matter as to which under these conditions he is entitled to be satisfied, or which he is entitled to require together with carriage therefore to and from the work. The contractor shall also supply without charge the requisite number of setting out works and counting weighing and assisting in the measurement or examination at any time and from time to time of the work or materials. Falling his so doing the same may be provided by the Engineer-in-charge at the expense of the contractor and the expenses may be deducted from any money due to the contractor under the contract and/or from his security deposit or the proceeds of sale thereof or of a sufficient portions thereof.

Work not to be sublet contract may be rescinded and security deposit forfeited for subletting, billing or if contractor becomes insolvent.

### CLAUSE 18:

The contract shall not be assigned or sublet without the written approval of the Engineer-in-charge and if the contractor shall assign or sublet his contract or attempt so to do, or insolvent or commence any insolvency proceedings of make any composition with his creditors or attempt so to do, or if any bride gratuity, loan perquisite, regard or advantage pecuniary or otherwise, shall either directly, be given promised or offered by the contractor, or any of his servants or agent to any public officer of person in the employ of government in any way relating to his office of employment, or if any such officer of person shall become in any way directly or indirectly interested in the contractor, the Engineer-in-charge on behalf of the I.I.T. (I.S.M.) shall have power to adopt any of the course specified in Clause 3 as he may deem best suited at the interest of I.I.T. (I.S.M.) and in the event of any of these coursed being adopted the consequences specified in the said Clause 3 shall ensure sum payable by way of reference to actual loss.

### CLAUSE 19:

Except where otherwise provided in the contract all questions and disputes relating to the meaning of specification, design, drawings and instructions here in before mention and as to the quality of workmanship or materials used on the work or as to any other question, claim, right matter or thing whatsoever in any way arising out of or relating to the contract, design, drawings, specifications, estimates, instructions, orders or these conditions or otherwise concerning the works, or the execution or failure to execute the same whether arising during the progress or the work or after the completion or abandonment thereof shall be referred to the sole arbitration of the person appointed by the Director/Indian Institute of Technology (Indian Institute of Technology (Indian School of Mines)), in charge of the work at the time of dispute or if there be no director, the Administrative head Registrar of the said Indian School of Mines at the time of such appointment. If will be no objection to any such appointment that the arbitrator so appointment is a I.I.T. (I.S.M.) Officer, that he has to deal with the matters

to which the contract relates and that in the course of his duties as I.I.T. (I.S.M.) Officer he had expressed views on all or any of the matters in dispute or difference. The arbitratory to whom the matter is originally referred being transferred or vacating his office or being unable to act for any reason such Director or Administrative head as aforesaid at the time of such transfer, vacation of office of inability to act, shall appoint another person to act as arbitrator in accordance with the terms of the contractor. Such person shall be entitled to proceed with the reference from the stage at which it was left by his predecessors. It is also a term of this contractor that no person other than a person appointed by such Director or Registrar, as aforesaid should act as arbitrator and if any reason that is not possible, the matter is not to be referred to arbitration at all. In all cases where the amount of the claim in dispute is E 55,000/- (Rupees Fifty five thousand) and above, the arbitrator shall give reason for the award.

Subject as aforesaid the provisions of the Arbitration Act, 1940, or any statutory modification or reenactment therefore and the rules made there under and for the time being in force shall apply to the arbitration proceeding under this clause.

It is also a term of the contract that the party invoking arbitration shall specify the dispite to be referred to arbitration under this clause together with the amount or amounts claimed in respect of each such dispute.

It is also a term of the contract that it the contractor(s) do/does not make any demand for arbitration in tespect of any claim(s) will be deemed to have been waived and absolutely beared and the ISM shall be discharged and released of all liabilities under the contract in respect of these claims.

The arbitrator(s) may from time to time with consent of the parties enlarge the time from making and publishing the awards.

The decision of Campus Engineer/Asstt. Campus Engineer regarding the quantum of reduction as well as justification thereof in respect of rates for substandard work which may be decided to be accepted will be final and would not be open to arbitration.

### Lump sum in estimates:

#### CLAUSE 20:

ON.

83

When the estimate on which a tender is made includes lump sums in respect of parts of the work the contractor shall be entitled to payment in respect of the items of work involved or the part of the work in question at the same rates, as are payable under this contract for the such items, or if the part of the work in question in not, in the opinion of the Engineer-in-charge payable of measurement, the Engineer-in-charge may at his discretion pay the lump sums amount entered in the estimate, and the certificate in writing of the Engineer-in-charge shall be final and conclusive against the contractor with regards to any sum or sums payable to him under the provisions of the clause.

### CLAUSE 21:

In the case of any class of work for which there is no such specification as is mentioned in Rule 1, such work shall be carried out in accordance with the local specification and in the event of there being no local specification, then in such case the work shall be carried out in all respect in accordance with the instructions and requirements of the Engineer-in-charge.

### CLAUSE 22:

ile nys go Withholding and lien in respect of sums claimed.

Whenever any claim or claims for payment of a sum of money arises out of or under the contract against the contractor, the Engineer-in-charge of the Government shall be entitled to withhold and also have a lien to retain such sum or sums in whole or in apart from the security, if any deposited by the contractor and for the purpose aforesaid, the Engineer-in-charge or the Government shall be entitled to withhold the security deposit if any, furnished as the case may be and also have a lien over the same pending finalization or adjudication of any such claim. In the event of the security being insufficient to cover the claimed amount or amounts or no security has been taken from the contractor, the Engineer-in-charge or the Director shall be entitled to with hold and have a lien to retain to the extent of such claimed amount of amounts referred to above from any sum or sums found payable to the contractor under the same contract or any other contract with the Engineer-in-charge or I.I.T. (I.S.M.) or any contracting person through the Engineer-in-charge pending finalization of adjudication of any such claim.

It is an agreed term of the contract that the sum of money or moneys so withheld or retained under the lien referred to above, by the Engineer-in-charge or Director fill the claim arising out of or under the contract is determined by the Arbitrator (if the contract is governed by the arbitration clause) by the competent court, as the case may be and that the contractor will have no claim for interest or damages whatsoever or any account in respect of such withholding or retention under the lien referred to above and duly notified as such to the contractor. For the purpose of this clause where the contractor is a partnership firm or a limited company, the amount or amounts whole or in pat from any sum found payable to any partner/limited company as the case may be whether in his individual capacity or otherwise.

#### CLAUSE 23:

Lien in respect of claims in other contracts:

Any sum of money due and payable to the contractor (including the security deposit returnable to him) under the contract may be with held or retained by way of lien by the Engineer-in-charge or the Director or any other contracting persons through Engineer-in-charge or I.I.T. (I.S.M.) or such other person or persons in respect of payment of a sum of money arising out of or under any other contract made by the contractor with the Engineer-in-charge or I.I.T. (I.S.M.) or with such other person or persons.

### CLAUSE 24:

The whole work may be spilled up between two or more contractors or accepted in part on not in entirely, if considered expedient.

### CLAUSE 25:

A II taxes except Goods & Service Tax (GST) as applicable in respect of this contract shall be payable by the contractor and IIT (ISM) will not entertain any claim whatsoever in this respect. GST will be paid along with the contractor's bill.

#### CLAUSE 26:

Without prejudice to any of the rights or remedies under this contract, if the contractor dies, the Executive Engineer or behalf of the I.I.T. (I.S.M.) shall have the option of terminating the contractor without compensation to the contractor.

### CLAUSE 27:

Before start of the work all materials are to be deposited and got inspected by Engineer-in-charge in terms of quality and quantity.

### CLAUSE 28:

The contractor will comply with all the provisions of minimum wage Act 1948, contract labour (Regulation and abolition) Act 1970 and rules framed there under and other labour laws effecting contract labour that may be brought into force from time to time.

#### CLAUSE 29:

dis.

The contractor is to indemnify on keeping hardness the employer from all claims for accidents loss or damage to his workmen through the operation of this contract.

### CLAUSE 30:

The Engineer-in-charge shall be at liberty to dismiss any pension employed by the contractor who in his opinion is unskillful or incompetent.

### CLAUSE 31:

The work is to be stopped during unfavorable weather at the description of the Engineer-in-charge and the contractor is to make any allowance required to cover any coats of loss of profit incurred through such stoppage.

#### CLAUSE 32:

A satisfactory work completion certificate from individual occupant/HODs may be obtained on completing the work by the contractor before measurement is taken.

#### CLAUSE 33:

The contractor shall ensure that they should have provident fund Code Number, if applicable and compliance of EPF & MPAct, 1952.

I have read the whole content of the above Conditions of contract undersigned and Agreed to abide by the above terms and Conditions.

Date:	
(Signature of Contractor)	Campus Engineer
Occupation:	
Address:	

Witness:

1)

2)